

## 16.02 Reinforced Plate Demagnetizer type DP

**Heavy duty construction, Innovative**

### Applications

Demagnetization

### Construction

. Extremely efficient automatic adjustment of magnetic field intensity depending on workpiece size . Reinforced system for up to 50 mm thick workpieces . For bigger workpieces we recommend tunnel demagnetizers . Maximum working temperature 45°C . Coil protected by aluminium housing . Protection class IP54 . During the demagnetization cycle the workpiece should be moved at low and constant speed through the alternative field of demagnetizer (recommended speed: 0,05 to 0.2 m/sec.) Included with purchase; - ON/OFF switch - 1.5 meter long cable - Fixing holes  
Voltage 230/400 VAC  
Duty cycle 100 %



Art.-N°16.02

Diagram below: dimensions in mm

Product	Weight	A	B	C	D	E	F	G	H
16.02.160	22,0	148	238	278	121	850VA	IP 54	230VAC	160
16.02.250	30,0	148	328	368	121	1380VA	IP 54	230VAC	250
16.02.400	46,0	148	478	518	121	2050VA	IP 54	230VAC	400
16.02.400.400	57,0	166	518	553	148	2860VA	IP 65	400VAC	400
16.02.500.400	67,0	166	618	653	148	3600VA	IP 65	400VAC	500
16.02.600.400	80,0	166	718	753	148	4420VA	IP 65	400VAC	600
16.02.650.400	88,0	166	768	803	148	4700VA	IP 65	400VAC	650
16.02.700.400	92,0	166	818	853	148	5000VA	IP 65	400VAC	700
16.02.800.400	105,0	166	918	953	148	5600VA	IP 65	400VAC	800
16.02.900.400	117,0	166	1018	1053	148	6300VA	IP 65	400VAC	900
16.02.1000.400	130,0	166	1118	1153	148	7000VA	IP 65	400VAC	1000

OPTIONS :

- Other sizes on request
- Other voltages on request
- Low frequency generator for demagnetization of difficult workpieces
- Automatic demagnetization systems



All right reserved to change construction and dimensions without notice - Print date :

---

Bridage, Magnétisme & Systèmes Sarl - 120 rue Jean Jaurès - F 92300 Levallois Perret  
Tél. 33 (0)1 80 87 61 69 - Fax 33 (0)1 80 87 61 70 - info@bms-industrie.com - www.bms-industrie.com