

30.10 Vacuum Unit type VAL

Heavy duty construction, Effective

Applications

Grinding , Milling , Machining , Planning , Clamping

Construction

. Vacuum pump with guaranteed reliability . 100% ensured operational vacuum performance and avoidance of idle run . Integrated buffer tank with 70 liter capacity . High speed also with slow pressure: 0.5 mbar . Silent operation . Air cooling . Standard motor connection . Motor standard IP55 class F . The required complementary equipment to be ordered: - 30.11 Safety switch - 30.12 Liquid separator - 30.14 Suction hose - 30.12P Included with purchase: - Start set - Air filter

Voltage 400 VAC

Duty cycle 100 %



Art.-N°30.10

Diagram below: dimensions in mm

Product	Weight	A	B	C	D	E	F	G	H
30.10.25.400	75,0	650	705	725	785	G1/2"	3x8/120°/550mm	26 m3/h	0.75kw
30.10.40.400	80,0	650	705	725	785	G1/2"	3x8/120°/550mm	42 m3/h	1.1kw

OPTIONS :
- 230 V execution



All right reserved to change construction and dimensions without notice - Print date :

Bridage, Magnétisme & Systèmes Sarl - 120 rue Jean Jaurès - F 92300 Levallois Perret
Tél. 33 (0)1 80 87 61 69 - Fax 33 (0)1 80 87 61 70 - info@bms-industrie.com - www.bms-industrie.com